



TL 5-1075-2022

Vydání č.: 1

Účinnost: 03.12.2022

Neautorizovaný tisk

## Flat component - Collar

### PRODUCT DESCRIPTION

Collar is a ring-shaped cut out of the waterproofing membranes.

### TECHNICAL PARAMETERS

The technical parameters of waterproofing membranes, from which are the components produced, are listed in the data sheets for individual types of membranes.

### MEMBRANE TYPE, DIMENSIONS, COLOUR

The membrane used				Collar diameter
Name	Thickness	Colour <sup>1)</sup>		
FATRAFOL 803	2.00	signal yellow	~ B4013 <sup>2)</sup>	400 mm ± 4 mm/ 20 mm ± 1 mm
		brown	~ RAL 8025	
FATRAFOL 804	2.00	red	~ RAL 3016	
		blue	~ RAL 5015	
		green	~ RAL 6000	
		dark grey	~ RAL 7012	
		black-grey	~ RAL 7016	
		black-grey	~ RAL 7021	
		light grey	~ RAL 7035	
		light grey	~ RAL 7040	
		copper brown	~ RAL 8004	
		brown	~ RAL 8025	
		white	~ RAL 9010	
		black	~ RAL 9011	
AQUAPLAST 805	2.00	green	~ RAL 6000	
		khaki	~ RAL 6006	
		olive	~ RAL 6014	
		black	~ RAL 9011	
EKOPLAST 806	1.50	black	~ RAL 9011	
FATRAFOL 810	1.50	light grey	~ RAL 7035	183 mm ± 3 mm/ 14 mm ± 1 mm
		light grey	~ RAL 7040	

<sup>1)</sup> Different colour shade of various batches of surfaces of the membranes may differ. Minor differences of colour shade do not constitute the matter for a possible claim.

<sup>2)</sup> internal designation (RAL not specified)

### USAGE

To create shaped pieces for circular penetrations through the waterproofing membrane.

## APPLICATION

The laying of components can be made by specialized and for this purpose trained firms at the constructions.

The components are applied conformable with fundamentals being set and described in a Construction and Technologic Instruction FATRAFOL-S, FATRAFOL-H a FATRAFOL-A, being valid in the time of waterproofing providing, available on [www.fatrafol.cz](http://www.fatrafol.cz).

## PACKAGING

- collar diameter 400 mm: 10-piece PE bag, 140-piece cardboard box
- collar diameter 183 mm: 100-piece PE bag, 400-piece cardboard box

## STORAGE

Store at temperature from -5 °C to +30 °C. There is necessary to protect the product from pollution at the building site and is recommended to protect it from weathering influences till the processing time.

## APPROVALS / CERTIFICATES

Listed in the technical data sheets for individual types of waterproofing membranes.

## MORE INFORMATION

More information can be found on the manufacturer's website [www.fatrafol.cz](http://www.fatrafol.cz).

## LEGAL CLAUSE

The technical data contained herein are based on our current knowledge and experience and relate to the use of products under normal application conditions. The information that is included in the current technical data sheet is provided according to a method of use and is incomplete. Before using this product, the user has to check whether the product is suitable for intended use. In addition to that, all the users should contact the dealer or manufacturer of this product to obtain further technical information regarding its use if they are of the opinion that the information available to them requires any explanation, for both the normal and specific use of this product. Please always check that you have the latest version of the product technical data sheet at your disposal. This data sheet and further information can be obtained from the sales or technical representative of the manufacturer or at the website of the producer.

## PRODUCER

Fatra, a. s., třída Tomáše Bati 1541, 763 61 Napajedla, Czech Republic

tel.: +420 577 50 3325 (1111)

e-mail: [studio@fatrafol.cz](mailto:studio@fatrafol.cz)

<http://www.fatrafol.cz>

